## Hardwood **PLYBRACE** Panel



The Gunnersen bracing range now includes 4.0mm thick hardwood plybrace panels that can achieve up to 7.5Kn per metre racking resistance when installed in accordance with the AS1684.2-2006 framing code.

High capacity bracing systems are capable of delivering better outcomes for modern house design. Importantly for merchants and fabricators, stocking Gunnersen 4.0mm hardwood bracing means you have all the common applications covered with one product.

When you build with Gunnersen Hardwood Plybrace you can be sure that you are using a product that complies with Australian standards, and that's because all Gunnersen hardwood bracing is mechanically stress graded at the point of manufacture.

In response to the growth in use of termite resistant framing, Gunnersen are also releasing the new 4.0mm bracing treated to H2-F level. This will make it the perfect partner for complete framing, Gunnersen are also releasing protection in areas south of the Tropic of Capricorn.



## **PLYBRACE** Panel

## **CERTIFICATION EVIDENCE**





Above Left: Letter from Watters Electrical Pty Ltd explaining that they have designed and manufactured a three point Modulus of Elasticity stress grading machine that has measured and determined that Gunnersen's Plybrace meets Australian and New Zealand standard AS/NZS 1604: 2004.

This equipment is regularly calibrated by engineers to ensure product quality and standards.

Above Right: Plybrace treatment is certified to ASNZ 1604 and the method of application is registered brand 940 73 H26 under the timber marketing act. 1977 (NSW) (Section 20) Approval of Preservative Treatment and Registration of Brand.

## PRODUCT AVAILABILITY CHART

	F27	PACK QTY
2440 x 900 x 4.0mm	yes	50/150
2440 x 1200 x 4.0mm	yes	50/150
2745 x 900 x 4.0mm	yes	50/150
2745 x 1200 x 4.0mm	yes	50/150
3050 x 900 x 4.0mm	yes	50/150
3050 x 1200 x 4.0mm	yes	50/150

